



# **WOODMASTER GT™**

## **Precision Ground Carbon Blades for Wood Cutting**

### EXCELLENT BLADE LIFE ON RESAWS AND PORTABLE SAWMILLS

Teeth are ground and induction hardened to keep the blade sharp

High carbon backing steel reduces band breaks and allows multiple sharpenings

#### SMOOTH, STRAIGHT CUTS AT PRODUCTION RATES

Deep gullet design effectively removes sawdust to minimize wavy cutting Durable tooth form cuts efficiently through hard knots

# CUTS A WIDE RANGE OF SOFT AND HARD WOODS

Precision set teeth cut a variety of wood types from pine and cedar to oak and maple

Optimized to cut the most difficult wood including seasoned and frozen timber





WIDTH X THICKNESS (IN)	HOOK ANGLE	SIDE SET	KERF (IN)	PRIMARY APPLICATION	TOOTH SPACING	1/2"	3/4"	7/8"	1"
					TPI	2	1.3	1.1	1.0
1 x .035	10°	.016"	.067"	Pallet Resaws/High Dust Removal		2002978			
1 x .035	10°	.022"	.079"	Pallet Resaws/General Purpose		2002979			
1 x .035	10°	.018"	.071"	Pallet Resaws/High Dust Removal			2002980		
1 x .035	10°	.022"	.079"	Pallet Resaws/General Purpose			2002981		
1-1/4 x .042	10°	.022"	.086"	General Purpose				1990159	
1-1/4 x .042	10°	.022"	.086"	General Purpose			2007841		
1-1/2 x .045	10°	.026"	.097"	General Purpose				2003000	
1-1/2 x .045	10°	.026"	.097"	General Purpose					2003075
1-1/2 x .055	10°	.026"	.107"	General Purpose				2003086	
1-1/2 x .055	10°	.026"	.107"	General Purpose					2003088

All coils are random length, palletized coils between 375 and 450 feet.





Key product specifications won't wear off during blade use, retaining pertinent information for sharpening. setting, and re-ordering



to the cutting face of raker teeth allowing for efficient cutting, extended blade life and more sharpenings



High carbon backing steel reduces band breaks and allows multiple sharpenings



#### **GROUND TOOTH GEOMETRY**

Teeth are ground and induction hardened to keep the blade sharp

Deep gullet design effectively removes sawdust to minimize wavy cutting





# **WOODMASTER GT™**

# **Sharpening Accessories**

### CBN wheels for use with Wood-Mizer® BMS Series

LENOX ITEM#	PRODUCT DESCRIPTION		WHEEL SIZE	TOOTH SPACING	HOOK ANGLE	RELIEF ANGLE
1990827	5" CBN Wheel for WOODMASTER GT	1.3	5"	3/4"	10°	30°
1990828	5" CBN Wheel for WOODMASTER GT	1.1	5"	7/8"	10°	30°
1990829	5" CBN Wheel for WOODMASTER GT	1.0	5"	1"	10°	30°
1990830	8" CBN Wheel for WOODMASTER GT	1.3	8"	3/4"	10°	30°
1990832	8" CBN Wheel for WOODMASTER GT	1.1	8"	7/8"	10°	30°
1990834	8" CBN Wheel for WOODMASTER GT	1.0	8"	1"	10°	30°



### CAM kits for use with Cook's Cat Claw™

LENOX ITEM #	PRODUCT DESCRIPTION	TPI	SHARPENER MANUFACTURER	TOOTH SPACING	HOOK ANGLE	RELIEF ANGLE
1990836	WOODMASTER GT Cook's Cat Claw Sharpening Kit	1.3	Cook's Cat Claw	3/4"	10°	30°
1990837	WOODMASTER GT Cook's Cat Claw Sharpening Kit	1.1	Cook's Cat Claw	7/8"	10°	30°
1990838	WOODMASTER GT Cook's Cat Claw Sharpening Kit	1.0	Cook's Cat Claw	1"	10°	30°



Customer Service: 800-628-8810 Technical Support: 800-642-0010

lenoxtools.com